



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		ADDED -1 Ø.668 REFERENCE DIMENSION, ADDED -3 MISSING .95 DIMENSION AND DATUM CONTROL FEATURES PER G.E. ADDED RB TO TOOL NO. PER RW.	10/5/2011	RJC	
2	16-0263	-1 CH'D DIM WAS Ø1.900 IS Ø1.90, CH'D NOTE WAS ENGRAVE T/N IS ENGRAVE T/N, S/N, "MADE IN USA". -15 MODIFIED DESCRIPTION WAS HOSE IS RED HOSE.	12/6/2016	SM	JAG







ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	PLUG	6061		2
			-3	1	SLEEVE	6061		3
		B/O	-5	2	O-RING	VITON FLUOROELASTOMER	030 (MCMaster-CARR #1201T43)	1
		B/O	-7	1	O-RING	VITON FLUOROELASTOMER	028 (MCMaster-CARR #1201T41)	1
		B/O	-9	1	O-RING	VITON FLUOROELASTOMER	015 (MCMaster-CARR #1201T26)	1
		B/O	-11	1	FITTING	BRASS	1/8 NPTF X 1/4 BARBED (MCMaster-CARR #91465K11)	1
		B/O	-13	1	FITTING	BRASS	1/4 NPTF X 1/4 BARBED (MCMaster-CARR #91465K91)	1
		B/O	-15	1	RED HOSE	RUBBER	1/2 OD X 2' (MCMaster-CARR #5405K2)	1

DART AEROSPACE																											
TITLE P3 LEAK CHECK ADAPTER																											
DWG NO. RB PWC70797	REV 2																										
<table border="0"> <tr> <td>MAT'L</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>HEAT TREAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH</td> <td>.XXX ± .005 FRACTIONS ± 1/8</td> </tr> <tr> <td></td> <td>.XX ± .01 ANGLES ± 5°</td> </tr> <tr> <td></td> <td>.X ± .1 SURFACES = 125°</td> </tr> <tr> <td>SPEC</td> <td>1. BREAK ALL SHARP EDGES</td> </tr> <tr> <td></td> <td>.015 x 45° OR .015R</td> </tr> <tr> <td>DRAWN BY: GILBERT</td> <td>2. DIMENSIONAL LIMITS APPLY</td> </tr> <tr> <td>CHECKED: CLOUGH</td> <td>AFTER PLATING</td> </tr> <tr> <td>OPPS APPR: ANDERSON</td> <td>3. INTERPRET DIM AND TOL PER</td> </tr> <tr> <td>QA APPR: LINDSAY</td> <td>ASME Y14.5M-2009</td> </tr> <tr> <td>APPROVED: GILBERT</td> <td>USED ON MODEL</td> </tr> <tr> <td></td> <td>BELL</td> </tr> </table>		MAT'L	UNLESS OTHERWISE SPECIFIED	HEAT TREAT	DIMENSIONS ARE IN INCHES	FINISH	.XXX ± .005 FRACTIONS ± 1/8		.XX ± .01 ANGLES ± 5°		.X ± .1 SURFACES = 125°	SPEC	1. BREAK ALL SHARP EDGES		.015 x 45° OR .015R	DRAWN BY: GILBERT	2. DIMENSIONAL LIMITS APPLY	CHECKED: CLOUGH	AFTER PLATING	OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER	QA APPR: LINDSAY	ASME Y14.5M-2009	APPROVED: GILBERT	USED ON MODEL		BELL
MAT'L	UNLESS OTHERWISE SPECIFIED																										
HEAT TREAT	DIMENSIONS ARE IN INCHES																										
FINISH	.XXX ± .005 FRACTIONS ± 1/8																										
	.XX ± .01 ANGLES ± 5°																										
	.X ± .1 SURFACES = 125°																										
SPEC	1. BREAK ALL SHARP EDGES																										
	.015 x 45° OR .015R																										
DRAWN BY: GILBERT	2. DIMENSIONAL LIMITS APPLY																										
CHECKED: CLOUGH	AFTER PLATING																										
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER																										
QA APPR: LINDSAY	ASME Y14.5M-2009																										
APPROVED: GILBERT	USED ON MODEL																										
	BELL																										
SCALE 1:2	DATE 5/12/2011																										
SHEET 1 OF 3																											

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		ADDED -1 Ø.668 REFERENCE DIMENSION PER G.E.	10/5/2011	RJC	
2	16-0263	-1 CH'D DIM WAS Ø1.900 IS Ø1.90, CH'D NOTE WAS ENGRAVE T/N IS ENGRAVE T/N, S/N, "MADE IN USA".	12/6/2016	SM	JAG




SECTION A-A

(-1)
 PLUG



DART AEROSPACE	
TITLE P3 LEAK CHECK ADAPTOR	
DWG NO. PWC70797-1	REV 2
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .005 FRACTIONS ± 1/8
FINISH	.XX ± .01 ANGLES ± 5°
SPEC MIL-A-8625F, TYPE II, CLASS III	.X ± .1 SURFACES = 125 ✓
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: CLOUGH	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	BELL
SCALE 1:1	DATE 5/12/2011
SHEET 2 OF 3	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		ADDED -3 MISSING .95 DIMENSION AND DATUM CONTROL FEATURES PER G.E.	10/5/2011	RJC	





2X $\phi 1.740$ O-RING
GROOVE ϕ



DETAIL D
SCALE 2 : 1



SECTION B-B



DETAIL C
SCALE 4 : 1
2 PLACES

NOTE: PIPE FITTING MUST NOT PROTUDE INTO THE
INTERIOR WHEN FULLY THREADED.

DART AEROSPACE	
TITLE P3 LEAK CHECK ADAPTOR	
DWG NO. PWC70797-3	REV 2
MAT'L 6061 HEAT TREAT FINISH SPEC MIL-A-8625F, TYPE II, CLASS II	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX \pm .005 FRACTIONS \pm 1/8 .XX \pm .01 ANGLES \pm 5° .X \pm .1 SURFACES = 125✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: GILBERT	USED ON MODEL
CHECKED: CLOUGH	BELL
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:2	DATE 5/12/2011
SHEET 3 OF 3	

(-3)

SLEEVE